

PO Box 458 · 1462 340<sup>th</sup> Street · Adair, Iowa 50002 Phone: 1-800-232-4742 · Fax: 1-800-282-3353 www.agridrain.com · email: info@agridrain.com

## Check Valves 🧩

## Helps prevent backflow in drainage lines.


 Must provide a stable base, and installation using flexible couplers is recommended.

 Horizontal installation in drainage systems helps keep basements from flooding.

- Eliminates backup in the field tile when creeks rise.
- Clean out with threaded plug allows easy maintenance and inspection.
- Fits SCH40 PVC pipe.
- Available in 3" and 4".

Check Valve Size	Overall Length	Total Height	OD of Stub
3"	7.56"	6.1"	3.937"
4"	11.18"	7.18"	5"

## Agri Drain Check Valves




- Constructed of rugged SDR35 PVC.
- Available with or without clean out.
- Clean out option with threaded plug allows easy maintenance and inspection.
- Full flow for drainage.
- Valves are not pressure rated.
- Valves are intended for gravity flow: Low pressure and some seepage will occur.
- Available in 6" through 12".

	9	
Check Valve Size	Overall Length	Stub Length
6"	17.75"	4"
8"	20.75"	4"
10"	21.25"	4"
12"	23.75"	4"



## Oversized Check Valves 🧩



- Must provide a stable base, and installation using flexible couplers is recommended.
- Body constructed of rugged, <sup>1</sup>/<sub>2</sub>"-thick PVC with SDR35 PVC stubs.
- Available with or without a clean out.
- Stainless steel screws and custom anodized aluminum corner extrusions used for strength and durability.
- Full flow for drainage.
- Valves are not pressure rated.
- Valves are intended for gravity flow: Low pressure and some seepage will occur.
- Available in 15" and 18".



Check Valve showing working parts and water flow direction.

Check Valve Size	Overall Length	Stub Length
15"	27.25"	4"
18"	31.25"	4"