info@agridrain.com



10" & 12" Valterra Gate Valves

Heavy-duty quality for use in industrial, agricultural, and commercial markets.

- Must provide a stable base, and installation using flexible couplers is recommended.
- Attaches to SCH40 PVC pipe.
- Unrestricted flow.
- Quick opening.
- Trouble-free simplicity.
- 100% water tested at factory.
- Quick shutoff in low pressure or vacuum lines.
- Other sizes available.



| Dimensions and Hub Depth | | | |
|--------------------------|---------|---------|--|
| | 10" | 12" | |
| Α | 35" | 35" | |
| В | 48.5" | 48.5" | |
| С | 18.475" | 18.475" | |
| D | 10.78" | 12.78" | |
| E | 19.625" | 18.625" | |
| F | 13.75" | 15.375" | |
| G | 5" | 6" | |
| Н | 10" | 10" | |

"B" Dimension is height of valve in fully open position

| Materials and Specifications | | | |
|------------------------------|---------|---------|--|
| | 10" | 12" | |
| Color | White | White | |
| Hubs | PVC | PVC | |
| Body | ABS | ABS | |
| Shaft | 304SS | 304SS | |
| Paddle | 304SS | 304SS | |
| Handle | 304SS | 304SS | |
| Seals | Sarlink | Sarlink | |
| Max PSI Open/Closed | 6/8 | 6/8 | |



WARNING: Cancer and Reproductive Harm—www.P65Warnings.ca.gov/

Extension Rod for Valterra Gate Valves

- Extension Rod for 10"-12" Valve
 - Stainless steel rod with cotter pin(s) for assembly. Can attach multiple extensions together to achieve greater height.
 - Available in 36" length.





