

Check Valves 🎉

Helps prevent backflow in drainage lines.

- Must provide a stable base, and installation using flexible couplers is recommended.
- Horizontal installation in drainage systems helps keep basements from flooding.
- Eliminates backup in the field tile when creeks rise.
- Clean out with threaded plug allows easy maintenance and inspection.
- Fits SCH40 PVC pipe.
- Available in 3" and 4".



- Must provide a stable base, and installation using flexible couplers is recommended.
- Constructed of rugged SDR35 PVC.
- Available with or without clean out.
- Clean out option with threaded plug allows easy maintenance and inspection.
- Full flow for drainage.
- Valves are not pressure rated.
- Valves are intended for gravity flow: Low pressure and some seepage will occur.
- Available in 6" through 12".






Check Valve Size	Overall Length	Stub Length
15"	27.25"	4"
18"	31.25"	4"



- Must provide a stable base, and installation using flexible couplers is recommended.
- Body constructed of rugged, ¹/₂"-thick PVC with SDR35 PVC stubs.
- Available with or without a clean out.
- Stainless steel screws and custom anodized aluminum corner extrusions used for strength and durability.
- Full flow for drainage.
- Valves are not pressure rated.
- Valves are intended for gravity flow: Low pressure and some seepage will occur.
- Available in 15" and 18".



Check Valve Size	Overall Length	Total Height	OD of Stub
3"	7.56"	6.1"	3.937"
4"	11.18"	7.18"	5"



	—		
Check Valve Size	Overall Length	Stub Length	
6"	17.75"	4"	
8"	20.75"	4"	
10"	21.25"	4"	
12"	23.75"	4"	