

Manufactured by:



PO Box 458 · 1462 340th Street · Adair, Iowa 50002
 Phone: 1-800-232-4742 · Fax: 1-800-282-3353
 www.agridrain.com · email: info@agridrain.com

Inline Water Level Control Structure™

- ◆ Available in manual or automated.
- ◆ Constructed of rugged ½" PVC with lockable plastic lid.
- ◆ Stainless steel screws and custom anodized aluminum corner extrusions used for strength and durability.*
- ◆ Flexible couplers allow PVC, plastic pipe, or other materials to be easily attached. *(Please specify type of pipe when ordering.)*
- ◆ Stoplogs made of PVC in 5" and 7" heights for adjustability. (Maintenance recommended: Remove stoplogs and grease seal with white lithium grease. Ensure there is no debris in the tracks or along the bottom of the structure. Replace stoplogs after greasing.)
- ◆ **Important!** To minimize seepage, align stoplogs firmly against one side of the stoplog track.
- ◆ Stoplogs must remain in track during structure installation.
- ◆ Structures are not pressure rated.
- ◆ Structures are intended for gravity flow: Low pressure and some seepage will occur.
- ◆ 5-year warranty on all standard structures.
- ◆ Customized or special orders will carry a 1-year warranty on workmanship and material and are nonreturnable.


**For water that is caustic, acid, corrosive, salt, or pH below 5 pH or above 9 pH, please notify us of your requirements to ensure structures are built with compatible hardware. For these applications, Agri Drain recommends stainless steel.*



US Patent No. 6,715,508 B2
 US Patent No. 6,786,234 B2
 Canadian Patent No. 2,403,456
 Canadian Patent No. 2,466,976

Comes with a handle to install and remove stoplogs.

Stoplog seal ensures a tight fit to prevent leakage.



Inline Water Level Control Structure™			
Pipe Size	Available Heights	Width	Depth
4"	2' - 12'	8"	10"
6"	2' - 12'	8"	10"
8"	2' - 12'	11 ⁵ / ₈ "	12"
10"	2' - 12'	14"	16"
12"	2' - 12'	16"	20"
15"	2' - 12'	20"	24"
18"	2' - 12'	24"	28"
24"	3' - 10'	31"	39"

Rugged injection molded stoplogs used in structures with 4", 6", 8", 10", and 12" pipe sizes.



PVC stoplogs with stainless steel lifting hooks used in structures with 15", 18", and 24" pipe sizes.



Stoplog Retainer

Hold extra stoplogs up & out of the way!

- ◆ Stainless steel retainer hooks to lowest stoplog that you want to hold up within your Inline Water Level Control Structure™.
- ◆ 10' of 3/16" nylon rope (included) attaches to the retainer and secures to the inner brace bar near the top of the structure.

